

DESCRIPTION - BEARINGS

1. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 90 MM; MATERIAL: BRS; OD 132MM; PART NO: H2320;
2. SLEEVE, COUPLING: TYPE: GEAR; DIMENSIONS: DIA 66 X LG 46 MM; MATERIAL: NYLON; REFERENCE NO: M28
3. SLEEVE, COUPLING: TYPE: GEAR; DIMENSIONS: DIA 63 X LG 28 MM; MATERIAL: NYLON; DAVID BROWN NYLOCON NUMBER 1, FOR USE WITH PFMILL
4. BEARING, ROLLER: TYPE: SELF ALIGNING; SPHERICAL; ROW: DOUBLE; INSIDE DIAMETER: 140 MM; OUTSIDE DIAMETER: 225 MM; WIDTH: 68 MM; BORE SHAPE: TAPER; DIMENSIONS, TO FIT WITHDRAWAL SLEEVE AHX3128; PART NO: 23128CCKW33C3
5. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 280 MM; LENGTH: 240MM; MATERIAL: STL; OD 300MM; REFERENCE NO: SKF-0H3260H;
6. BEARING, ASSEMBLY: TYPE: ROLLER; INSIDE DIAMETER: 75 MM; OUTSIDE DIAMETER: 130 MM; WIDTH: 52 MM; SPHERICAL SELF ALIGNING, DOUBLE ROW, LINK BELT, EXTENDED CONE, COMPLETE WITH: TWO OILSEALS, ONE STEEL LOCK NUT, TWO STEEL GRUB SCREWS SIZE M10, FOR USE ON GRIZZLY CHAIN CONVEYOR TAKEUP/HEADSHAFT; PARTNO: B224ML75
7. BEARING, ROLLER: TYPE: SLEW RING; ROW: SINGLE; INSIDE DIAMETER: 715 MM; OUTSIDE DIAMETER: 979 MM; WIDTH: 100 MM; WITHOUT GEAR, NUMBER OF HOLES, OUTER RING 28, INNER RING 28, GREASE NIPPLES ON OUTER RING; PART NO: RKS22302-5707 XX,
8. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 140 MM; OUTSIDE DIAMETER: 250 MM; WIDTH: 68 MM; PART NO: 22228CCKW33,
9. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 108 MM; LENGTH: 114MM; MATERIAL: STL; SIZE 127MM OD; PART NO: H2324,
10. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 125 MM; LENGTH: 13MM; MATERIAL: STL; 148MM OD; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; PART NO: H2328,
11. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 50 MM; LENGTH: 45MM; MATERIAL: STL; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; PART NO: H311,
12. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 75 MM; LENGTH: 63MM; MATERIAL: STL; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; SIZE 110MM OD; PART NO: H317
13. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 90 MM; LENGTH: 71MM; MATERIAL: STL; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; SIZE 130MM OD; PART NO: H320,
14. BEARING, ROLLER: TYPE: SELF ALIGNING; SPHERICAL; ROW: DOUBLE; INSIDE DIAMETER: 85 MM; OUTSIDE DIAMETER: 150 MM; WIDTH: 36 MM; BORE SHAPE: TAPER; NOTE - THE REFERENCE NUMBER MUST BE CAST AND NOT ENGRAVED ON AND ORIGINAL PACKED, COMPLETE WITH H317 ADAPTOR SLEEVE; REFERENCE NO: 22217CCK; REFERENCE NO: 22217CCKC3;

15. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 170 MM; OUTSIDE DIAMETER: 288 MM; WIDTH: 88 MM; NOTE - ITEM MUST BE ORIGINAL PACKED; MODEL NO: 23134 CCK
16. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 150 MM; LENGTH: 122MM; MATERIAL: STL; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PACKED AND MARKED; SIZE 220MM OD; PART NO: H3134, SUPPLIER:
17. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 80 MM; LENGTH: 65MM; MATERIAL: STL; OD 90MM; PART NO: H318;
18. BEARING, ROLLER: TYPE: SELF ALIGNING; SPHERICAL; ROW: DOUBLE; INSIDE DIAMETER: 85 MM; OUTSIDE DIAMETER: 150 MM; WIDTH: 36 MM; PART NO: 22217CK,
19. BEARING, BALL: TYPE: DEEP GROOVE; ROW: SINGLE; INSIDE DIAMETER: 35 MM; OUTSIDE DIAMETER: 80 MM; WIDTH: 21 MM; STYLE: DOUBLE SEAL; PART NO: 6307-2RS,
20. BEARING, BALL: TYPE: CONRAD; ROW: SINGLE; INSIDE DIAMETER: 30MM; OUTSIDE DIAMETER: 62 MM; WIDTH: 16 MM; STYLE: DOUBLE SEAL; PART NO: 6206-2RS
21. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 60 MM; LENGTH: 50MM; MATERIAL: STL; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; OD 65MM; PART NO: H313,
22. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 115 MM; LENGTH: 92MM; MATERIAL: STL; SUPPLIER NOTE - THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; SIZE 165MM OD; PART NO: H3126;
23. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 125 MM; LENGTH: 96MM; MATERIAL: STL; SUPPLIER NOTE – THE ITEM MUST BE ORIGINAL PROTECTIVE PACKED AND MARKED; SIZE 145MM OD; PART NO: H3128E
24. BEARING, BALL: TYPE: CONRAD; ROW: SINGLE; INSIDE DIAMETER: 25MM; OUTSIDE DIAMETER: 62 MM; WIDTH: 17 MM; STYLE: DOUBLE SHIELD; PART NO: 6305-2Z,
25. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 110 MM; OUTSIDE DIAMETER: 200 MM; WIDTH: 69.85 MM; REFERENCE NO: 23222C; PART NO: 23222CC3,
26. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 140 MM; OUTSIDE DIAMETER: 250 MM; WIDTH: 88 MM; NOTE: ITEM MUST BE ORIGINAL PACKED; MODEL NO: 23228 CCK-W33

27. BEARING, ROLLER: TYPE: CYLINDRICAL; ROW: SINGLE; INSIDE DIAMETER: 30 MM; OUTSIDE DIAMETER: 72 MM; WIDTH: 19 MM; REFERENCE NO: N306;
28. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 180 MM; LENGTH: 150MM; MATERIAL: STL; NOTE - THE ITEM MUST BE PROTECTIVE PACKED AND CLEARLY MARKED; SIZE 200MM OD; SNL3140; PART NO: OH3140
29. BEARING, ROLLER: TYPE: SELF ALIGNING; SPHERICAL; ROW: DOUBLE; INSIDE

- DIAMETER: 65 MM; OUTSIDE DIAMETER: 120 MM; WIDTH: 31 MM;BORE SHAPE: TAPER; PART NO: 22213CK
30. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 110 MM; LENGTH: 88MM; MATERIAL: STL; M120 X 2MM THREAD, 83.3 TAPER PER METRE IN MM 1:12 ON DIA; SIZE 125MM OD; PART NO: H3124, SUPPLIER:
 31. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 135 MM; LENGTH: 115MM; MATERIAL: STL; 160MM OD; REFERENCE NO: H3130
 32. EARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 120 MM; OUTSIDE DIAMETER: 215 MM; WIDTH: 58 MM; PART NO: 22224CCK/W33,
 33. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 140 MM; OUTSIDE DIAMETER: 250 MM; WIDTH: 68 MM; PART NO: 22228CKW33STD,
 34. BEARING, ROLLER: TYPE: SELF ALIGNING; SPHERICAL; ROW: DOUBLE;INSIDE DIAMETER: 130 MM; OUTSIDE DIAMETER: 230 MM; WIDTH: 64 MM;BORE SHAPE: TAPER; PART NO: 22226CCKC3W33
 35. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 160 MM; LENGTH: 132MM; MATERIAL: STL; 187MM OD; PART NO: H3136,
 36. BEARING, PILLOW BLOCK: ROLLING ELEMENT: SPHERICAL; BLOCK SIZE: WD 96 X LG 400 X HT 255 MM; SHAFT HEIGHT: 127.5 MM; BOLT MOUNTING: 2; BOLT DIAMETER: 25 MM; INSIDE DIAMETER: 155 MM; HOUSING MATERIAL: CI; SHAFT DIAMETER: 110MM, 185MM WIDE, 271MM LONG; DUTY: HEAVY; PART NO: SNA524-620,
 37. BEARING: TYPE: ROLLER; TAPER; MATERIAL: STL; INSIDE DIAMETER:150 MM; OUTSIDE DIAMETER: 270 MM; WIDTH: 154 MM; STYLE: OPEN; SET, DYNAMIC 1250000N AND STATIC 2280000N; PART NO: 02BX130GR
 38. BEARING, SLEEVE: TYPE: SPHERICAL; INSIDE DIAMETER: 155 MM;OUTSIDE DIAMETER: 206 MM; LENGTH: 114 MM; MATERIAL: STL; COOPER ROLLER SET, CONSIST OF BEARING AND CARTRIDGE; PART NO:02BC130EX,
 39. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 170 MM; LENGTH: 140MM; MATERIAL: STL; 200MM OD; REFERENCE NO: H3138; PART NO:H3138, BEARING, ROLLER: TYPE: CONE/CUP; TAPER; ROW: SINGLE; INSIDEDIAMETER: 85 MM; OUTSIDE DIAMETER: 180 MM; WIDTH: 45 MM; PART NO: FAG31317,
 40. DIAMETER: 240 MM; OUTSIDE DIAMETER: 400 MM; WIDTH: 128 MM; PART NO: 23148CCKW33C3,
 41. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 220 MM; OUTSIDE DIAMETER: 370 MM; WIDTH: 120 MM; PART NO: 23144EW33KFC3
 42. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 200 MM; OUTSIDE DIAMETER: 340 MM; WIDTH: 112 MM; PART NO: 23140BKMB3,
 43. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 190 MM; OUTSIDE DIAMETER: 320 MM; WIDTH: 104 MM; REFERENCE NO: 23138CCKW33; PART NO: 23138 CCK/W33C3
 44. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 190 MM; OUTSIDE DIAMETER: 320 MM; WIDTH: 104 MM; REFERENCE NO: 23138CCKW33; PART NO: 23138 CCK/W33C3
 45. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 220 MM; LENGTH: 170MM;

MATERIAL: STL; 240MM OUTSIDE DIAMETER, 172MM WIDTH; 250 MM OD;
REFERENCE NO: 0H3148H

46. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 300 MM; OUTSIDE DIAMETER: 540 MM; WIDTH: 192 MM; BORE SHAPE: TAPER; PART NO: 23260CACKW33C3,
47. BEARING, ROLLER: TYPE: CONE/CUP; TAPER; ROW: DOUBLE; INSIDE DIAMETER: 200 MM; OUTSIDE DIAMETER: 360 MM; WIDTH: 218 MM; OUTER RING AND INNER CONE, INDIRECT TYPE, COMPLETE WITH SPACER RING FOR PRELOAD; REFERENCE NO: E32240; REFERENCE NO: E432240
48. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 80 MM; LENGTH: 52MM; MATERIAL: STL; 93MM OD, FOR PLUMMER BLOCK; REFERENCE NO:H218; REFERENCE NO: H218F; PART NO: H218 F, SUPPLIER: UNKNOWN;PART NO: H218,
49. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 87 MM; LENGTH: 90MM; MATERIAL: STL; COMPLETE WITH LOCK NUT KM19 AND LOCKING DEVICE MB19; SIZE 100MM OD; REFERENCE NO: H2319
50. BEARING, BALL: TYPE: DEEP GROOVE; ROW: SINGLE; INSIDE DIAMETER:50 MM; OUTSIDE DIAMETER: 130 MM; WIDTH: 31 MM; STYLE: OPEN;PART NO: 6410C3,
51. SLEEVE, ADAPTOR: TYPE: BEARING; LENGTH: 83 MM; MATERIAL: STL; WITHDRAWAL; INSIDE DIAMETER: 135 MM; OUTSIDE DIAMETER: 140 MM;REFERENCE NO: SKF-AHX 3128;
52. EARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 100 MM; OUTSIDE DIAMETER: 180 MM; WIDTH: 46 MM; REFERENCE NO: 22220CCKW33; PART NO: 22220CCKW33C3,
53. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: DOUBLE; INSIDE DIAMETER: 110 MM; OUTSIDE DIAMETER: 200 MM; WIDTH: 53 MM; CYLINDRICAL BORE WITH W33 FEATURE; PART NO: 22222CCW33C3
54. BEARING, ROLLER: TYPE: SELF ALIGNING; ROW: SINGLE; INSIDE DIAMETER: 90 MM; OUTSIDE DIAMETER: 160 MM; WIDTH: 40 MM; FEEDER END STATION; PART NO: 22218CCKW3C3,
55. BEARING, SLEEVE: TYPE: BUSH; INSIDE DIAMETER: 50 MM; OUTSIDE DIAMETER: 93 MM; LENGTH: 90 MM; MATERIAL: STL; FOR USE WITH DUST HANDLING PLANT BOOT STATION; PART NO: RHK-30100-030,
56. BEARING, SLEEVE: TYPE: BUSH; INSIDE DIAMETER: 85 MM; OUTSIDE DIAMETER: 112 MM; LENGTH: 92 MM; MATERIAL: SS; A.S.G. IRON, BS SPECIFICATION: 3468-AUS 202A, VALVE MANUFACTURER: BLAKEBOROUGH AND SON; DRAWING NO: 51632B; REFERENCE NO: 32; PART NO: 35353-148,
57. BEARING, PILLOW BLOCK: ROLLING ELEMENT: SPHERICAL; BLOCK SIZE: WD 90 X LG 320 X HT 183 MM; SHAFT HEIGHT: 95 MM; BOLT MOUNTING: 2; BOLT DIAMETER: M22; INSIDE DIAMETER: 97 MM; HOUSING MATERIAL: CI; SELF ALIGNING, MEDIUM DUTY, COMPLETE WITH DOUBLE LIP SEAL; PART NO: SNH 517 TG, BEARING, PILLOW BLOCK: BLOCK SIZE: WD 234 X LG 600 X HT 400 MM;
58. SHAFT HEIGHT: 210 MM; BOLT MOUNTING: 4; BOLT DIAMETER: M36; INSIDE DIAMETER: 180 MM; HOUSING MATERIAL: CI; HOUSING, COMPLETE WITH LOCATING RINGS, LABYRINTH SEAL WITH O SECTION CORD TS40; REFERENCE NO: FRB10/340; PART NO: SD3140, SUPPLIER

59. BEARING, PILLOW BLOCK: ROLLING ELEMENT: ROLLER; BLOCK SIZE: WD 125 X LG 445 MM; SHAFT HEIGHT: 150 MM; BOLT MOUNTING: 2; BOLT DIAMETER: M25; INSIDE DIAMETER: 115 MM; HOUSING MATERIAL: CI; SPHERICAL SELF ALIGNING, COMPLETE WITH DOUBLE LIP SEALS; SEALING ARRANGEMENT: LABYRINTH (STL AND NBR O-RING, IT CAN TAKE UP TO 120DEG C); PART NO: SN526
60. BEARING, PILLOW BLOCK: ROLLING ELEMENT: ROLLER CYLINDRICAL; BLOCK SIZE: WD 190 X LG 540 MM; SHAFT HEIGHT: 180 MM; BOLT MOUNTING: 4; BOLT DIAMETER: M30; INSIDE DIAMETER: 164 MM; HOUSING MATERIAL: CI; USED ON ASH PLANT; DUTY: HEAVY; PART NO: SD3136,
61. BEARING, PILLOW BLOCK: ROLLING ELEMENT: SPHERICAL; BLOCK SIZE: WD 150 X LG 505 X HT 294 MM; SHAFT HEIGHT: 150 MM; BOLT MOUNTING: 2; BOLT DIAMETER: 35 MM; INSIDE DIAMETER: 176 MM; HOUSING MATERIAL: STL; PLUMMER BLOCK, WITHOUT SEALS; DUTY: HEAVY; PART NO: SNA528,
62. BEARING, PILLOW BLOCK: ROLLING ELEMENT: SPHERICAL; BLOCK SIZE: WD 175 X LG 550 X HT 420 MM; SHAFT HEIGHT: 180 MM; BOLT MOUNTING: 4; BOLT DIAMETER: M20; INSIDE DIAMETER: 294 MM; HOUSING MATERIAL: CI; COOPER SPLIT PLUMMER BLOCK, ITEM: 140,130 UNLOCATED, SET; DUTY: HEAVY; PART NO: 02BCP130EX, BEARING, PILLOW BLOCK: ROLLING ELEMENT: SPHERICAL; BLOCK SIZE: WD 214 X LG 390 X HT 290 MM; SHAFT HEIGHT: 145 MM; BOLT MOUNTING: 2; BOLT DIAMETER: 23 MM; INSIDE DIAMETER: 166 MM; HOUSING MATERIAL: CI; FOR USE ON SCREW FEEDER; DUTY: HEAVY; END COVER TO BE SUPPLIED WITH PLUMMER BLOCK; PART NO: B510,
63. WD 214 X LG 390 X HT 290 MM; SHAFT HEIGHT: 145 MM; BOLT MOUNTING: 2; BOLT DIAMETER: 23 MM; INSIDE DIAMETER: 166 MM; HOUSING MATERIAL: CI; FOR USE ON SCREW FEEDER; DUTY: HEAVY; END COVER TO BE SUPPLIED WITH PLUMMER BLOCK; PART NO: B510,
64. BEARING, FLANGE BLOCK: BOLT MOUNTING: 4; SHAPE: SQ; HOUSING MATERIAL: CI; INSIDE DIAMETER: 75 MM; BOLT DIAMETER: M19; BLOCK SIZE: LG 200 X THK 80 MM; SPHERICAL; REFERENCE NO: UCF215; PART NO: FY75,
65. BEARING, PILLOW BLOCK: BLOCK SIZE: WD 200 X LG 525 X HT 350 MM; SHAFT HEIGHT: 180 MM; BOLT MOUNTING: 4; BOLT DIAMETER: 28 MM; INSIDE DIAMETER: 195 MM; HOUSING MATERIAL: CI; DUTY: MEDIUM; REFERENCE NO: SD3136TS
66. BEARING, ROLLER: TYPE: SPLIT; ROW: DOUBLE; INSIDE DIAMETER: 300 MM; OUTSIDE DIAMETER: 495.3 MM; WIDTH: 193 MM; CAGE MATERIAL: CAST IRON; STYLE: OPEN; WITH CARTRIDGE 02C300MM AND FELT SEAL; PART NO: 02BC300MMEX,
67. BEARING, ROLLER: TYPE COOPER SPLIT, SINGLE ROW, 150 MM INSIDE DIAMETER, 254 MM OUTSIDE DIAMETER, 98.40 MM WIDTH, H7 INTERNAL FIT, FFT: LIGHT DUTY SERIES, LOCATING TYPE, FOR USE ON ASH CONDITIONERS, BEARING MUST USE THE FELT SEAL, PART NUMBER: SRB SPLIT-LSM150BR, COOPER SPLIT- 01B150GR *
68. SLEEVE: TYPE: WALL BOX; DIMENSIONS: ID 110 X OD 210 X THK 20 MM; MATERIAL: SS 316; APPLICATION: BLOWER; FLANGE SIZE: 210 MM OD X 110 MM ID X 20 MM THK, PCD: 186 MM, FOUR HOLES 16 MM, RECESS 132 MM X 4 MM DEEP, COMPLETE WALL SLEEVE WITH THE MOUNTING FLANGE FITTED; MATERIAL SPECIFICATION 3.2 WELDER QUALIFICATIONS; ESKOM WELDING RULE BOOK REQUIREMENTS; FIG NO: 14; PART NO: DSPQ 2702,

69. BEARING, ROLLER: TYPE: TAPER; ROW: DOUBLE; INSIDE DIAMETER: 120 MM; OUTSIDE DIAMETER: 215 MM; WIDTH: 74.22 MM; BORE SHAPE: SPHERICAL; STYLE: SELF ALIGNING; COMPLETE WITH ADAPTOR SLEEVE 82324; PART NO: 23224CKC3,
70. BEARING, ROLLER; TYPE SPHERICAL TAPER, INSIDE DIAMETER 135 MM, OUTSIDE DIAMETER 270 MM, WIDTH 73 MM, CAGE MATERIAL STL, USED ON ADAP TOR SLEEVE FOR SHAFT , ART NUMBER: 22230CCK/W33/C3
71. BEARING, BALL: TYPE: DEEP GROOVE; ROW: SINGLE; INSIDE DIAMETER: 25 MM; OUTSIDE DIAMETER: 52 MM; WIDTH: 15 MM; STYLE: DOUBLE SHIELD; IBI: VA228; CAGE MATERIAL: STL; HIGH TEMPERATURES, FOR USE ON LONG LAN OF IK545; PART NO: 90110-0024,
72. BEARING: TYPE: SPHERICAL; MATERIAL: STL; INSIDE DIAMETER: 150 MM; OUTSIDE DIAMETER: 270 MM; WIDTH: 96 MM; STYLE: TAPER; RATING: 1080 KN; PRESSURE RANGE: 1460 KN; PART NO: 23230 CCK
73. SLEEVE, ADAPTOR: TYPE: BEARING, TAPER LOCK; SHAFT SIZE: 135 MM; LENGTH: 139 MM; MATERIAL: STL; TO FIT BEARING 23230CCK/W3; PART NO: H2330;
74. BEARING: TYPE: SEAL AIR FAN; MATERIAL: STL; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 112 MM; WIDTH: 90 MM; STYLE: DOUBLE SEAL; NON-LOCKING BEARING; USED ON HORIZONTAL TUBE MILLS TRUNNING; SERIAL NO: SNEB224M45_ENG
75. BEARING: TYPE: SEAL AIR FAN; MATERIAL: STL; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 112 MM; WIDTH: 90 MM; STYLE: DOUBLE SEAL; LOCKING BEARING; USED ON HORIZONTAL TUBE MILLS TRUNNING; SERIAL NO: SNB224M45H_ENG;
76. BEARING, SLEEVE: TYPE: SPHERICAL; INSIDE DIAMETER: 110 MM; OUTSIDE DIAMETER: 180 MM; LENGTH: 85 MM; MATERIAL: STL; WITH TWO SEALS SEALING ARRANGEMENT; REFERENCE NO: GE120D0-2RS;
77. BEARING, BALL: TYPE: CONRAD; ROW: SINGLE; INSIDE DIAMETER: 45 MM; OUTSIDE DIAMETER: 100 MM; WIDTH: 25 MM; STYLE: DOUBLE SEAL; PART NO: 63092RSC3,
78. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 85 MM; LENGTH: 68 MM; MATERIAL: STL; SIZE 100MM OD; REFERENCE NO: H319;
79. SLEEVE, ADAPTOR: TYPE: BEARING; SHAFT SIZE: 140 MM; LENGTH: 147 MM; MATERIAL: STL; 173MM OD; 83.3MM TAPER PER METRE INMM, 1:12 ON DIAMETER; REFERENCE NO: H2332
80. BLOCK, PILLOW: 85 MM BORE, MATERIAL CAST IRON, FFT: SPECIAL MANUFACTURED WITH LOCATING RINGS, FRW 12, 5-170, END COVER-ASNH 519, FOR USE ON SSC RETURN SHAFT L/R 3 & 4, PART NUMBER: SSN HD 222519 SPL
81. HOUSING, BEARING UNIT: TYPE: PLUMBER BLOCK; MATERIAL: CI; SIZE 5MM SHAFT, FOR LINK BELT, PCD: 190.5MM, OD 222.2MM; PART NO: FCB224M75.H, SUPPLIER: UNKNOWN;